

# DS-KH6352-WTDE6 4-Wire Hybrid HD Indoor Station



- 7-inch TFT touch screen with 1024 × 600 resolution
- Receive calls, open the door and live view remotely
- Plug & Play
- Hik-Connect mobile control



## SpecificationSystem parameters

| System parameters          |  |
|----------------------------|--|
| Operation system           | Embedded Linux operation system                                  |
| ROM                        | 32 MB  |
| RAM                        | 128 MB   |
| Processor                  | Embedded high performance processor                              |
| Display parameters         |  |
| Screen size                | 7-inch   |
| Operation method           | Capacitive touch screen  |
| Туре                       | Colorful TFT   |
| Resolution                 | 1024 × 600   |
| Luminance                  | 250 cd/m² (Typ)  |
| Viewing Angle              | Horizontal 160°, vertical 130°                                   |
| Contrast                   | 700 (Typ)  |
| Audio parameters           |  |
| Audio input                | 1 built-in omnidirectional microphone                            |
| Audio compression standard | G.711U, G.711A   |
| Audio output               | 1 built-in loudspeaker   |
| Audio compression bitrate  | 64 Kps   |
| Audio quality              | Noise suppression and echo cancellation                          |
| Capacity                   |  |
| Linked indoor extensions   | 2  |
| capacity                   | 2  |
| Linked doorphone capacity  | 2 analog doorphones  |
| Analog Camera              | 1  |
| Network parameters         |  |
| Wi-Fi                      | Wi-Fi 802.11 b/g/n   |
| Device interfaces          |  |
| Alarm input                | 2  |
| Network interface          | 1  |
| RS-485                     | 1  |
| TF card                    | Support TF card, up to 128 G                                     |
| Alarm output               | 1  |
| Four-Wire interface        | 4  |
| Power interface            | 1  |
| Debugging port             | 2  |
| Relay                      | /  |
| General                    |  |
| Button                     | 0 physical button(s)   |
| Installation               | Surface mounting   |
| Indicator                  | /  |
| Weight                     | With package: 708g (1.56 lb), Without package: 260 g (0.5973 lb) |
| Working temperature        | -10 °C to 50 °C (14 °F to 122 °F)                                |
| Working humidity           | 10% to 90% (no-condensing)                                       |





| Dimension (W $\times$ H $\times$ D) | 175 mm × 113.5 mm × 18.1 mm (6.89" × 4.47" × 0.71")  |
|-------------------------------------|--|
| Power supply                        | 12 VDC   |
| Application environment             | Indoor   |
| Power consumption                   | ≤ 5 W  |
| Language                            | English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese (Brazil), Spanish, Hebrew, Romanian, Turkish, Estonian, Danish, Swedish, Norwegian, Finnish, Vietnamese, Croatian, Slovenian, Serbian, Arabic, Portuguese (Portugal), Lithuanian, Uzbek, Kazakh, Mongolian, Ukrainian, Latvian, Traditional Chinese |
| Material                            | Plastic  |


#### Available Model

DS-KH6352-WTDE6

### Dimension







Unit: mm [inch]

### Accessory

### Optional





Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision Corporate Channel



6 hikvisionhq