DS-7632NXI-K2(E)(2LAN)
32-ch 1U K Series AcuSense 4K NVR





- Adopt Hikvision AcuSense technology to minimize manual effort and security costs
- Efficient playback with AcuSearch technology
- Accurate perimeter protection effectively reduces false alarms
- Automatic cameras connection and configuration
- Up to 32-ch IP camera inputs
- H.265+/H.265/H.264+/H.264 video formats
- Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@2MP decoding capacity
- Up to 256 Mbps incoming bandwidth


▪ Specification

Model		DS-7632NXI-K2(E)(STD)
Intelligent Analytics	AI by NVR	Facial recognition, perimeter protection, motion detection 2.0, AcuSearch
	AI by Camera	Facial recognition, perimeter protection, motion detection2.0, ANPR
AcuSearch	By Camera	All channels *: The camera should enableAcuSearchfunction
Perimeter Protection	By NVR	Video analysis (HDnetwork camera,H.264/H.265) for human and vehicle recognition to reduce falsealarm. Up to 4 MP : 2-ch; 5 MPto 8 MP : 1-ch
	By Camera	All channels
Facial Recognition	Facial Detection and Analytics	Facepicturecomparison, human face capture, face picture search
	Facial Detection and Analytics Performance	Up to 4 MP: 2-ch; 8 MP to 5 MP: 1-ch
	Face Picture Comparison	8-ch
	Face Picture Library	Up to 16 facepicture libraries, with up to 50,000 face pictures in total (eachpicture ≤ 1 MB, total capacity ≤ 1 GB)
Motion Detection 2.0	By NVR	All channels, up to 4 MP (when enhanced SVCmode is enabled, up to 8 MP) video analysisfor human and vehiclerecognition to reduce falsealarm
	By Camera	All channels
Video and Audio	IPVideo Input	32-ch
	IP Speaker Input	4-ch
	Incoming Bandwidth	256 Mbps
	Outgoing Bandwidth	160 Mbps
	Video Output Mode	HDMI/VGA independent output
	HDMI Output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	VGA Output	1-ch, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
	Audio Output	1-ch, RCA(Linear, 1 KΩ)
	Two-Way Audio	1-ch, RCA(2.0 Vp-p, 1 KΩ,usingthe audio input)
Decoding	Decoding Format	H.265/H.265+/H.264/H.264+
	Recording Resolution	16 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF *: 16 MP is only availablefor channel 1.

	Synchronous playback	16-ch
	Decoding Capability	AI on: 2-channel 12 MP@30 fps, 4-channel 8 MP@30fps, 5-channel 6 MP@30 fps, 8-channel 4 MP@30 fps, 10-channel 3 MP@30fps, 16-channel 2 MP@30fps AI off: 3-channel 12 MP@30 fps, 5-channel 8 MP@30 fps, 6-channel 6 MP@30fps, 10-channel 4 MP@30 fps, 13-channel 3 MP@30fps, 20-channel 2 MP@30fps
	Stream Type	Video, Video and Audio
	Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2
Network	Remote Connection	128
	API	ONVIF (profile S/G); SDK;ISAPI
	Compatible Browser	IE11, Chrome 91, Firefox 88, Safari 12, Edge91,or above version
	Network Interface	2, RJ-4510/100/1000 Mbps self-adaptiveEthernet interface
	Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Auxiliary Interface	SATA	2 SATAinterfaces
	Capacity	Up to 16 TBcapacity for each HDD
	AlarmIn/Out	4/1
	USBInterface	Front panel: 1 × USB2.0; Rear panel: 1 × USB2.0
General	GUI Language	English, Russian, Bulgarian, Hungarian, Greek,German, Italian, Czech,Slovak,French, Polish, Dutch, Portuguese, Spanish, Romanian, Turkish, Japanese,Danish, Swedish,Norwegian, Finnish, Korean,Traditional Chinese,Thai, Estonian, Vietnamese, Croatian, Slovenian, Serbian, Latvian, Lithuanian, Uzbek, Kazakh,Arabic, Hebrew, Ukrainian, Indonesian
	Fan	Supports automatic speed control
	Power Supply	12 VDC,3.33 A
	Consumption	≤ 15 W (without HDD)
	Working Temperature	-10 °Cto 55 °C(14 °Fto 131 °F)
	Working Humidity	10%to 90%
	Dimension (W × D × H)	384 mm × 317 mm × 52 mm (15.12 × 12.48 × 2.03 inch)
	Weight	≤ 2kg (without HDD,4 lb.)
Certification	CE	EN55032: 2015, EN61000-3-2, EN61000-3-3, EN50130-4, EN55035: 2017
	Obtained Certification	CE,CB,REACH,WEEE,UKCA,RCM,IC


• Physical Interface

DS-7632NXI-K2(E)



Number	Description	Number	Description
1	LAN network interface	7	VGA interface
2	Audio out	8	USB interface
3	Audio in	9	12VDC power supply
4	HDMI interface	10	GND
5	Alarm in	11	Power button
6	Alarm out		

DS-7632NXI-K2(E)/2Lan




Number	Description	Number	Description
1	LAN network interface	7	VGA interface
2	Audio out	8	USB interface
3	Audio in	9	12VDC power supply
4	HDMI interface	10	GND
5	Alarm in	11	Power Button
6	Alarm out		

▪ Available Model


DS-7632NXI-K2(E)(STD)

▪ Dimension



Unit:mm [inch]

SCALE	1:1



Unit:mm [inch]

SCALE	1:1

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®