

DS-K4T100 Pro Series Bolt Electric Lock



- Electric bolt, polished and brushed stainless steel, support thrust of 800kg
- Working current: 900mA(Startup current), 100mA (standby), 12VDC + 10%
- Capable of 500,000 locking operations
- Suitable for wooden door, glass door, metal door and fireproof door
- Signal output of door lock status.

▪ Specification

General	
Power supply	12 VDC+10 %, 900 mA (startup current), 100 mA (standby)
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	0 to 95 % (relative humidity)
Dimensions	Lock Body: 205 mm × 35 mm × 40 mm (8.07" × 1.38" × 1.57") Armature Plate: 90 mm × 25 mm × 2 mm (3.54" × 0.98" × 0.07") Bolt: 16 mm × 16 mm (0.63" × 0.63")
Material	Bolt: polished and brushed stainless steel
Thrust	Max. 800 kg (1764 lb)
Door type	Glass door, wooden door, metal door, fireproof door
Signal output	Signal output NC, COM contact of door status
Magnetic induction distance	8 mm (0.31")
Delay duration	0/3/6/9 s optional

▪ Available Model

DS-K4T100

▪ Accessory

▪ Included

DS-K4T100-U2 Pro Electric Bolt Locks	DS-K4T100-U1 Pro Series Bolt Electric Lock Bracket
	

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



▪ **Optional**

**DS-K4T100-U
Pro Series Bolt
Electric Lock
Bracket**



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

