



TP-Link Omada POE380S PoE adapter 10 Gigabit Ethernet

Brand : TP-Link

Product family: Omada

Product code: POE380S

Product name : Omada PoE++ Injector



- 2 x 10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps/10 Mbps RJ45 ports ensure faster transmission
 - Complies with IEEE802.3af/at/bt standards, supplies up to 90 W
 - Reduces infrastructure costs by transmitting data and power simultaneously via an Ethernet cable
 - Automatically determines and supplies the exact power to meet the device's need
 - Wall-mounting and desktop design accommodates most installation scenarios
 - Plug & Play installation, no configuration required
 - Integrated power supply
 - Durable metal casing
- 1 x 10 Gbps RJ45 In, 1x 10 Gbps RJ45 Out, 90 W max out, 155x70x42 mm

[TP-Link Omada POE380S PoE adapter 10 Gigabit Ethernet:](#)



90W 10G PoE++ Injector

Unlocks peak performance for your 10G/Multi-Gig bandwidth and devices

10G Ports Ensure Faster Connection

Auto-negotiation for 6-speed (10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps /10 Mbps)

Auto Detect the Required Power, Up to 90 W

Standard 802.3af/at/bt for Various Powered Devices

Network		Operational conditions	
Ethernet interface type	10 Gigabit Ethernet	Operating temperature (T-T)	0 - 45 °C
Ethernet LAN data rates	10,100,2500,10000 Mbit/s	Operating relative humidity (H-H)	10 - 90%
Cabling technology	1000/10000	Storage temperature (T-T)	-40 - 70 °C
Power over Ethernet (PoE)	✓	Storage relative humidity (H-H)	5 - 90%
Networking standards	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u	Weight & dimensions	
Features		Width	155 mm
Product colour	Black	Depth	70 mm
LED indicators	PoE, Power	Height	42 mm
Ports & interfaces		Packaging content	
RJ-45 input ports	1	Number of products included	1 pc(s)
RJ-45 output ports	1	Quick installation guide	✓
Power		Technical details	
AC adapter input voltage	100 - 240 V	Sustainability compliance	✓
AC adapter frequency	50 - 60 Hz	Sustainability certificates	CE, Federal Communications Commission (FCC), RoHS
Input current	1.6 A		



4895252506341



4895252506358

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.